

## HIGH SPEED SINGLE SPOOLER



### Features:

- Pintle type with pneumatic bobbin loading.
- PLC speed synchronization control with speed detecting accumulator.
- For high speed take up of wire drawing and wire extrusion line a hard wire end pick out wheel to be fitted for wire drawing machine spooling.

### HIGH SPEED SINGLE SPOOLER

Model	Bobbin dia. (mm)	Load wt(kg)	Wire dia. (mm)		Pay off speed (mpm)		
			Copper conductor	Insulated wire	Wire drawing	High speed extrusion	Low speed extrusion
FHTP-40	300 - 400	150	0.4-2.6	1.4 - 3.0	1800	1200	600
FHTP -50	400 - 500	250	0.5 - 3.2	1.8 - 4.0	1800	1200	600
FHTP - 63	500 - 630	500	0.6 - 4.0	2.5 - 5.0	1600	1000	450
FHTP - 80	630 - 800	800	1.2 - 5.0	3.5 - 7.0	1200	800	450

**The machine specification is subject to change without notice.**

**Progressive Machinery Inc. Wire Packaging, Wire Manufacturing Machines World Wide**  
 Progressive Machinery Inc.  
 76 Ridley Rd. Bldg D, Suite 16  
 St. Catharines, ON L2S 3Y8  
[www.progmach.com](http://www.progmach.com)  
[Contact Information](#)

North America **1-905-346-0998**  
 Toll Free Tel: **1-866-918-0595**  
 Fax: **1-905-641-1082**  
[Email Us Directly](#)