

VERTICAL ACCUMULATORS



Features:

- Pulleys U type groove or V type groove.
- O.D of accumulation pulleys 250 / 300/ 350/ 400 / 450 mm.
- Number of pulleys 10+11 / 9+10 / 7+8 sheaves
- Pulleys made of aluminum alloy with hardness treatment.
- Length About 3.0 Meters. (In Length) or we can manufacture to requirements.
- Accumulation Capacity Please refer to the specification table.
- Equipped with electric control box to control tension, power on/off and pulley carriage forward / backward.
- Equipped with pulley stand with rollers as inlet /outlet wire guide.

Application

- To be installed in an Extrusion, CV's and Rewind Lines to accumulate or control Payoff or Take-up during Reel change over.

Vertical Accumulator

MODEL	Power Clutch (kg-m)	Number of pulleys	Accumulation Capacity (m)	Wire Dia. (mm)
FHVAC-250	10	10+11	40	Φ1~Φ 4
FHVAC-300	20	10+11	41	Φ2~Φ 6
FHVAC-350	20	9+10	38	Φ4~Φ 11
FHVAC-400	20	7+8	30	Φ6~Φ12
FHVAC-450	20	7+8	31	Φ8~Φ13

Machine specification is subject to change without notice.

Progressive Machinery Inc. Wire Packaging, Wire Manufacturing Machines World Wide

Progressive Machinery Inc.
76 Ridley Rd. Bldg D, Suite 16
St. Catharines, ON L2S 3Y8

www.progmach.com

[Contact Information](#)

North America **1-905-346-0998**

Toll Free Tel: **1-866-918-0595**

Fax: **1-905-641-1082**

[Email Us Directly](#)